


*En fonction du matériel utilisé

 GRÂCE À L'IRC 98, UN RENDU DES COULEURS EXCEPTIONNEL

CARACTÉRISTIQUES TECHNIQUES

Puissance	Réf.	IP	Température de couleur
10W	824011 	-	-


-  0 IP20  03 3000K  880 lm/m
-  4 IP65*  04 4000K  1000 lm/m
-  5 IP67*



- ▶ Coupe 10W = Tous les 2.5cm
 0 - 2.5 - 5 - 7.5 - 10 - 12.5 - 15 - 17.5 - 20 - 22.5 - 25 - 27.5 - 30 - 32.5 - 35 - 37.5 - 40 - 42.5 - 45 - 47.5 - 50 - 52.5 - 55 - 57.5 - 60 - 62.5 - 65 - 67.5 - 70 - 72.5 - 75 - 77.5 - 80 - 82.5 - 85 - 87.5 - 90 - 92.5 - 95 - 97.5 - 100

Puissance	Réf.	IP	Température de couleur
20W	830011 	-	-


-  0 IP20  03 3000K  1800 lm/m
-  4 IP65*  04 4000K  1870 lm/m
-  5 IP67*



 PAS DE COUPE ULTRA PRÉCIS 16mm

Puissance	Réf.	IP	Température de couleur
21W	842011 	-	-

-  0 IP20  03 3000K  2110 lm/m
-  4 IP65  04 4000K  2186 lm/m
-  5 IP67



- ▶ Autre couleurs disponibles, nous consulter selon vos besoins.
- ▶ Coupe 20W et 21W = Tous les 1.6cm
 0 - 1.6 - 3.2 - 4.8 - 6.4 - 8 - 9.6 - 11.2 - 12.8 - 14.4 - 16 - 17.6 - 19.2 - 20.8 - 22.4 - 24 - 25.6 - 27.2 - 28.8 - 30.4 - 32 - 33.6 - 35.2 - 36.8 - 38.4 - 40 - 41.6 - 43.2 - 44.8 - 46.4 - 48 - 49.6 - 51.2 - 52.8 - 54.4 - 56 - 57.6 - 59.2 - 60.8 - 62.4 - 64 - 65.6 - 67.2 - 68.8 - 70.4 - 72 - 73.6 - 75.2 - 76.8 - 78.4 - 80 - 81.6 - 83.2 - 84.8 - 86.4 - 88 - 89.6 - 91.2 - 92.8 - 94.4 - 96 - 97.6 - 99.2 - 100.8
- ▶ Références également disponibles en longueurs de 5 m en ajoutant /5 à la fin de votre référence